







C D3875-1LXX FLOOR PROTECTOR (206B)

NOTES:
1) MATERIAL: SEE TABLE C
2) FINISH: NONE
3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
4) UNITS: INCHES UNLESS OTHERWISE NOTED
5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
6) IDENTIFICATION: IDENTIFY WITH DART P/N "D3875-1" PER DART QSI 044 METHOD 6.4
7) WEIGHT: 3.81 lbs
8) TOOLING: THERMOFORM PER MOLD DT9475 PER QSI 022. TRIM PER MOLD.
9) MINIMUM MATERIAL THICKNESS AFTER FORMING IS 0.050" EXCEPT WHERE SHOWN
10) EDGE FLANGE MAY BE TRIMMED FOR FIT BY CUSTOMER, AS REQUIRED.

C

PART NUMBER	DESCRIPTION
D3874-1L02	F6006 SUEDE/POLISHED 701 BLACK LEXAN SHEET 0.125 THICK (REF DART SPEC MLEX.125-F6006-02)
D3874-1L08	90318 PROTECT-A-GLAZE 112 CLEAR LEXAN SHEET 0.118 THICK (REF DART SPEC MLEX.118-90318-08)

PRELIMINARY ISSUE

REV.	DESCRIPTION	BY	DATE
C	ADDED D3875-1L02 CONFIGURATION AND RE-IDENTIFIED D3875 AS D3874-1L08. REVISED NOTE 1 AND ADDED MATERIAL TABLE.	AK	14.04.10
B	19.5 WAS 18.6 MIN (ZN B3-1), 45.0 WAS 45.2 (ZN D6-1), 1.1 MIN. WAS 0.5 MIN. (ZN B8-1)	DB	13.04.09
A	NEW ISSUE	PH	09.01.29

DESIGN	AK	**DART AEROSPACE LTD** HAWKESBURY, ONTARIO, CANADA
DRAWN	AK	
CHECKED	VS	DRAWING NO. D3875 REV. C2
MFG. APPR.	DL	SHEET 1 OF 1
APPROVED		TITLE FLOOR PROTECTOR SCALE NTS
DE APPR.		
DATE	14.04.10	

COPYRIGHT © 2009 BY DART AEROSPACE LTD
THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.